



### Electrical Specifications

#### Input

Input Voltage (VAC)	120V-277V (+/- 10%)	
Frequency Range (Hz)	50 - 60 Hz (+/- 5%)	
	<b>120V</b>	<b>277V</b>
Input Current (A)	0.8	0.33
THD @ Full load	<20%	<20%
Power Factor @ Full load	>0.9	>0.9
Efficiency @ Full load	≥90%	≥91%
Inrush Current (Apk) <sup>2</sup>	31.8	82.2
Line Regulation	< 5%	< 5%

**2** - Complies to NEMA 410 inrush current requirements

#### Output

Output Current (mA)	700-2000mA (1mA step) 2000mA default
Output Voltage (VDC)	20-54VDC
Output Ripple Current	<25% @ 2000mA
Max. Output Power (W)	75W <sup>3</sup>
LED Power-Up Time	< 0.5sec CA T-24 Compliant
Load Regulation	<3%
Over Voltage Protection	Yes, non-latching
Over Load Protection	Yes, non-latching
Output Short-Circuit Protection	Yes, non-latching
Over Temperature Protection	Foldback to 50% at 100°C

**3** - 74W LED + 1W Aux on AUX models

#### Dimming

Dimming Control	0 - 10V (Isolated)
Dimming Range <sup>4</sup>	1-100%
Dimming Type	Current Reduction
Dimming Input Isolation	2.5kV
Source/Sink Current	0.6mA (max)
Dim-to-Off OFF/ON	0.7V/1V
Dim-to-Off Standby Power	< 1W
Dimming Interface Protection	Yes, 120-277Vac

**CAUTION: More than one power supply present.**

**4** - Driver can be dimmed to TRUE 1% level (7mA) of the programmed output current of the driver. Programmable with 1mA resolution with ± 3% accuracy

#### Auxiliary Output (For AUX models only)

Output Voltage (VDC)	12/20/24V (configurable)
Output Power (W)	1W Max
Voltage Regulation	±10%

#### LED thermal protection (NTC)

NTC Value Active Range	≤25kΩ
Temperature Derating Start	User defined

External NTC cannot leave the fixture.  
The PRG/ NTC control circuit terminals or lead wires are not isolated.

### General Information

Item Number	*2743XV (58014) (1%, F-type) *274A3U (58015) (1%, J-type) *2743XW (58016) (1%, F-type, AUX) *274A3W (58017) (1%, J-type, AUX)
Type	Constant Current
Output Power	75W (Max.)
Programming Tool	*274A17 (51645) and *2743V0 (57493)
Software	<a href="#">Download</a>
Programmable Features	Output Current Soft start, Dim-to-Off Dimming Level LED thermal protection Constant lumen output End-of-life indicator Vaux (12/20/24V)

Find (NAED) as cross reference for new item number i.e. \*12345


### Environmental Specifications

Ambient Operating Temperature	-40°C to 45°C
Max. Case Temperature (Tc)	85°C Max 80 °C (50kHrs) <sup>1</sup>
Max. Storage Temp.	75°C
Max. Relative Humidity (%)	85% non-condensing
Transient Protection	ANSI C82.77 Low Bay 2.5kV EFT according to: IEC61000-4-4 Level 3
UL Environmental Rating	Dry & Damp
UL File number	UL File #320395
IP Rating	IP20
EMI Compliance	FCC Part 15 Class A
Sound Rating	Class A

**1** - 5 year warranty applicable at 80°C



## Wiring Diagram



**Note:** - Maximum suggested remote mounting distance is 16 feet.

- Wire extraction tool is needed to extract the wires from the connectors. (WAGO Part#- 210-719).
- Use solid copper wire only: 16-20 AWG. Strip as below for all wires.
- DGND can be used as AUX return path.



- For wiring the output ports for the LED load, Vaux and DIM wire, 16 to 22 AWG is acceptable for use.

For more detailed information and requirements, consult the light engine information and or information pertaining to the light engine connectors.




## Key Application Notes

- Dim-to-off and Soft Start are programmable (enable/disable) features. The default mode for both features is disabled for out-of-the-box products. If these features are required, they must be enabled in the programming software.


## Mechanical Specifications

Housing	F-Style	J-Style
Length	6.3" (160mm)	6.3" (160mm)
Width	3.0" (77mm)	3.0" (77mm)
Height	1.2" (27.5mm)	1.2" (27.5mm)
Mounting Length	5.9" (150mm)	2.0" (50.8mm)
Mounting Width	3.0" (77mm)	3.0" (77mm)


## Mechanical Diagram - F-Style Housing



## Mechanical Diagram - J-Style Housing




## Operating Range




## Dimming Curves

### 0-10V Dimming




### Dim-To-Off Hysteresis




---

### Power Factor vs Input Voltage (Full Load)





---

### THD vs Input Voltage (Full Load)




## Efficiency vs Output Voltage




---

Power Factor vs Output Power



---

THD vs Output Power



## Inrush Characteristic

Vin (V)	Ipeak (A)	T(@ 10% of Ipeak)
120	31.8	100 μs
277	82.2	100 μs

Complies to NEMA 410 inrush current requirements

## Dimmer/Sensor Compatibility

Manufacturer	Part Number
Digital Lumens, Inc.	45678
Encelium LMS	EN-ILCM-1R10V-GB2-BK EN-ILCM-1R10V-GB2-BK/DR EN-ALC-1R10V-GB2-BK EN-ALC-1R10V-GB2-BK/DR
Leviton	IP710-DLZ
Lutron	DVTV-XX
Wattstopper	ADF-120277
Synergy lighting Controls	ISD BC

**Note:** The absence of a dimmer from this chart does not necessarily imply incompatibility. Please reference the dimmer manufacturer's instructions for installation.

## End-of-Life Indicator

The End-of-Life indicator helps the end user to receive a signal from the fixture indicating that it has reached its programmed life-time. After the LED driver reaches the programmed life-time, whenever it is turned ON, it stays at "Dim" level (10%) for 10 minutes and reaches its appropriate level.


## Constant Lumen Maintenance

The Constant Lumen Maintenance feature of the OTi75W helps to maintain the required lumen output of the fixture at a constant level throughout its lifetime. In general LED's lumen output will depreciate over time and in order to maintain sufficient light level towards the end of lifetime, the LED's are driven at high current initially and will result in more energy consumption. The constant lumen maintenance will give the flexibility to drive the LEDs at optimal driving current throughout its lifetime. This helps in energy savings, constant light output and enhanced reliability of the system.


## LED Thermal Protection (NTC) Characteristic

The LED thermal protection feature of the OTi75W helps reduce the temperature of the LED module by reducing the output current in case of abnormal temperature conditions. To use this feature a third party NTC thermistor should be connected to the LED power supply as shown in the wiring diagram below.

**With AUX**





**Without AUX**




In the end application, care must be taken to place the NTC thermistor close to the hottest spot on the LED module. If LED thermal protection is not required the NTC port on the LED power supply connector can be left open. Vishay, EPCOS, Murata, Panasonic are some of the manufacturers of NTC thermistor. EPCOS part number for reference only **B57164K153J (15kΩ @ 25°C)**. Murata part number for reference only - **NCP03XH223J05RL (22kΩ @ 25°C)**. Please refer to LED Thermal Protection App Note at: [https://media.osram.info/im/img/osram-dam-2219344/downloads/DL\\_Segmentation\\_\(EN\).pdf](https://media.osram.info/im/img/osram-dam-2219344/downloads/DL_Segmentation_(EN).pdf)

**Note:** Graphs for reference. The derating limits can be programmed using the OT Programmer (\*274A17).



---

## Lifetime vs Tc



---

## Warranty

eldoLED OPTOTRONIC® Products are covered by a 5-year limited warranty.  
Complete warranty terms can be found at: [www.eldoled.com/legal/terms-and-conditions](http://www.eldoled.com/legal/terms-and-conditions)

### eldoLED

One Lithonia Way  
Conyers, GA 30012  
United States

+1 877 353 6533

nasupport@eldoLED.com  
www.eldoLED.com

ECS-387 11-21

©2021 Acuity Brands Lighting, Inc.  
Specifications subject to change without notice. Actual performance may differ as a result of end-user environment and application.